



### Interior

## Step 3 Control Clear Mold Resistant Paint 69000

#### Product Description:

Step 3 Control Mold Resistant Paint is a clear 100% acrylic water-based coating for use on most interior surfaces susceptible to mold growth. The advanced formulation contains a fungistatic agent to resist mold growth on the dry coating surface. Step 3 Control is a durable, flexible, and breathable coating and has been tested by independent and certified laboratories to prove resistance to mold growth on the surface of the coating, and has successfully passed both ASTM G-21 and ASTM D-3273 mold resistance testing with the highest scores possible. This clear coating is ideal for areas which are not typically painted such as attic and basements.

For best results use Storm System Step 1 and Step 2 prior to Step 3.

#### Recommended Use:

Surfaces in household areas such as: bathrooms, basements, attics, mud rooms, laundry rooms and garages.

#### Application:

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Surface to be painted must be free of dust, mildew, dirt, grease, wax, loose paint or any other contaminant that may inhibit good adhesion.

- Clean and remove stains from the surface with Step 1 Clean Hydrogen Peroxide Cleaner.
- After cleaning, disinfect surface with Step 2 Kill Disinfectant & Deodorizer.

This product is ready-to-use as it comes from the container, but can be thinned sparingly with water as necessary. Apply with a nylon or polyester brush, 3/8" nap synthetic roller or airless spray using a .015 to .019 tip. Surface temperatures should be 50°F (10°C) or higher during application and drying time.

#### Precautions:

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not add solvents, oil or color in oil or mix with other paint types. Do not apply when air or surface temperature is below 50°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only. The coating is resistant to mold only on the surface of the coating. No mold resistance claim is made other than to the coating itself. The use of this product does not protect users or others against foodborne or disease-causing bacteria, viruses, germs or other disease-causing organisms.

#### Safety Information:

CAUTION! KEEP OUT OF REACH OF CHILDREN. Do not take internally. Close container after each use. Keep from freezing. Store between 40°F (4.5°C) and 90°F (32°C) 24 hour Emergency "CHEM-TEL" - 800.255.3924

#### Product Specifications:

<b>Type:</b>	100% Acrylic
<b>Exposure:</b>	Interior
<b>Specular Gloss:</b>	44° ± 3 @ 60°
<b>Volume Solids:</b>	25.8% ± 2
<b>Solids by Weight:</b>	28.8 % ± 2
<b>Viscosity @ 70 °F:</b>	85-90 KU ± 5
<b>Maximum VOC:</b>	90 g/liter
<b>Flash Point:</b>	Non-Combustible
<b>Thinner:</b>	Water
<b>Clean-Up:</b>	Soap & Water
<b>Available Colors:</b>	Clear
<b>Package Sizes:</b>	1 Gallon (8.7 lbs./gal)
<b>Drying Times:</b>	1 hr. to touch 2-4 hrs. to recoat
<b>Coverage:</b>	300-350 ft. <sup>2</sup> Smooth 175-300 ft. <sup>2</sup> Porous <small>(Spray Application is 50% of above)</small>
<b>Application:</b>	
Brush:	Synthetic, Nylon or Polyester
Roller:	3/8" Nap Synthetic Fiber
Airless Spray:	.015 to .019 Tip